

The DC130L series is a corrosion resistant mini LED based wall pack designed to provide the long life and high reliability required in industrial and commercial applications.

The housing can be mounted directly over a standard 4" box.

Suitable for wet locations, IP66 rated, these lights provide illumination for safety and security along building perimeters.

### Features & Benefits

- Uses up to 88% less energy when compared to the HID equivalent
- Instant on/off operation
- Resistant to shock and vibration
- Surged Protected
- Unique optical design provides optimum light distribution
- 4000K color temperature ‡
- CRI > 60
- Power factor > 0.98
- Produces no UV radiation
- Contains no Mercury
- 5 year limited warranty

### Applications

- Parking areas
- Entrances
- Walkways
- Underpasses
- Loading docks
- Recreation areas

For photometric data and IES files, please contact the factory.



### Product Specifications

#### Housing:

Durable die cast aluminum with a continuous one piece gasket ensures a weather tight seal.

#### Lens:

Clear Prismatic Borosilicate glass refractor

#### LEDs:

Array of 16 x 1 watt Philips Lumileds, providing 1600lm

#### Operating Voltage:

100 ~ 277 VAC 50/60Hz

#### Finish:

Dark bronze powder paint finish is standard.

#### Approvals / Ratings:

IP66 rated

Conforms to UL8750 & EN61347 safety regulations



UNDERWRITERS  
LABORATORIES



### Part Number Listing

Part No.	Series Number	Efficacy	Operating Voltage	Input Watts
R910001	DC130L	65lm/W	100~277 VAC 50/60 Hz	21W

\* Other finishes may be available. Contact the factory for details. ‡ Contact factory for details and other options.

So that we may continue to supply the best available products, specifications may change. Check our web site for the latest updates and product improvements. Contact our engineering staff if you require further application information.

# PARAFLEX INDUSTRIES

The Manufacturers Source For  
Lighting Parts And Products

DC130L  
Mini 16W  
LED Wall Pack

## Dimensions

