

The DC150L series is corrosion resistant medium wall pack designed to meet the rugged demands of industrial and commercial applications.

The housing can be mounted directly over a standard 4" outlet box or surface wired through ½" conduit entries.

Suitable for wet locations, these lights provide illumination for safety and security along building perimeters.

Features & Benefits

- Uses up to 88% less energy when compared to the HID equivalent
- Instant on/off operation
- Resistant to shock and vibration
- Surged Protected
- Unique optical design provides optimum light distribution
- 4000K color temperature ‡
- CRI > 60
- Power factor > 0.98
- Produces no UV radiation
- Contains no Mercury
- 5 year limited warranty

Applications

- Parking areas
- Entrances
- Walkways
- Underpasses
- Loading docks
- Recreation areas

For photometric data and IES files, please contact the factory.



Product Specifications

Housing:

Durable die cast aluminum with ½" threaded conduit entries for surface wiring. A continuous one piece gasket ensures a weather tight seal

Lens:

Clear Prismatic Borosilicate glass refractor

LEDs:

Array of 32 x 1 watt Philips Lumileds, providing 3200lm

Operating Voltage:

100 ~ 277 VAC 50/60Hz

Finish:

Dark bronze powder paint finish is standard.

Approvals / Ratings:

IP66 rated

Conforms to UL8750 & EN61347 safety regulations



UNDERWRITERS
LABORATORIES



Part Number Listing

Part No.	Series Number	Efficacy	Operating Voltage	Input Watts
R910003	DC150L	72lm/W	100~277 VAC 50/60 Hz	34W

* Other finishes may be available. Contact the factory for details. ‡ Contact factory for details and other options.

So that we may continue to supply the best available products, specifications may change. Check our web site for the latest updates and product improvements. Contact our engineering staff if you require further application information.

Dimensions

