

The DC560L series is corrosion resistant medium round back flood light, 11"x8", designed to meet the rugged flood light demands found in both industrial and commercial applications.

Suitable for wet locations, these lights provide illumination for safety and security.

Heavy duty swivel provides directional flexibility.

### Features & Benefits

- Uses up to 88% less energy when compared to the HID equivalent
- Instant on/off operation
- Resistant to shock and vibration
- Surged Protected
- Unique optical design provides optimum light distribution
- 4000K color temperature ‡
- CRI > 60
- Power factor > 0.98
- Produces no UV radiation
- Contains no Mercury
- 5 year limited warranty

### Applications

- Building facades
- Landscaping
- Signs and display
- Parking areas
- Walkways
- Loading docks



### Product Specifications

#### Housing:

Durable die cast aluminum with a silicon gasket to ensure a weather tight seal. Integral locking teeth swivel provides multiple adjustment intervals.

#### Lens:

Clear heat and impact resistant tempered glass.

#### LEDs:

Array of 32 x 1 watt Philips Lumileds, providing 3200lm.

#### Operating Voltage:

100 ~ 277 VAC 50/60Hz

#### Finish:

Dark bronze powder paint finish is standard.

#### Approvals / Ratings:

IP66 rated

Conforms to UL8750 & EN61347 safety regulations



UNDERWRITERS  
LABORATORIES



LED  
Flood Lights

For photometric data & IES files, contact the factory.

### Part Number Listing

Part No.	Series Number	Efficacy	Operating Voltage	Input Watts
R930002	DC560L	70lm/W	100 ~ 277 VAC 50/60Hz	34W

\* Other finishes may be available. Contact the factory for details. ‡ Contact factory for details and other options.

So that we may continue to supply the best available products, specifications may change. Check our web site for the latest updates and product improvements. Contact our engineering staff if you require further application information.

## Dimensions

