

The DCSHM200L-90 is a vandal and corrosion resistant large wall sconce, designed to meet the rugged demands of industrial and commercial applications with a European flair.

The housing can be mounted directly over a standard 4" outlet box. Suitable for wet locations, these lights provide illumination for safety and security along building perimeters.

The unique zero sight line feature allows this product to meet the local "Dark Sky" requirements.

Features & Benefits

- Uses up to 88% less energy when compared to the HID equivalent
- Instant on/off operation
- Resistant to shock and vibration
- Surged Protected
- Unique optical design provides optimum light distribution
- 4000K color temperature ‡
- CRI >60
- Power factor > 0.98
- Produces no UV radiation
- Contains no Mercury
- 5 year limited warranty

Applications

- Parking areas
- Entrances
- Walkways
- Underpasses
- Loading docks
- Recreation areas

For photometric data and IES files, please contact the factory.



LED
Wall Pack

Product Specifications

Housing:

Durable die cast aluminum with a continuous one piece gasket ensures a weather tight seal.

Lens:

Clear tempered glass lens

LEDs:

Array of 32 x 1 watt Philips Lumileds, providing 3200lm

Operating Voltage:

100 ~ 277 VAC 50/60Hz

Finish:

Dark bronze powder paint finish is standard.

Approvals / Ratings:



UNDERWRITERS
LABORATORIES



IP 66 rated

Conforms to UL8750 & EN61347 safety regulations



Part Number Listing

Part No.	Series Number	Efficacy	Operating Voltage	Input Watts
R910008	DCSHM200L-90	71lm/W	100 ~ 277 VAC 50/60Hz	34W

* Other finishes may be available. Contact the factory for details. ‡ Contact factory for details and other options.

So that we may continue to supply the best available products, specifications may change. Check our web site for the latest updates and product improvements. Contact our engineering staff if you require further application information.

Dimensions

