

The WPS99 series is corrosion resistant small wall pack designed to meet the rugged demands of industrial and commercial applications. The housing can be mounted directly over a standard 4" outlet box or surface wired through ½" conduit entries. Suitable for wet locations, these lights provide illumination for safety and security along building perimeters.



## Product Specifications

### Housing:

Durable die cast aluminum with three ½" threaded conduit entries for surface wiring or photocell installation. A continuous one piece gasket ensures a weather tight seal.

### Lens:

Clear Prismatic Borosilicate glass refractor

### Reflector:

One piece anodized aluminum reflector for maximum lumen output

### Socket:

Medium Base E26 – HID units  
Universal four-pin – Compact fluorescent

### Lamps:

Metal Halide 100W Max, High Pressure Sodium 150W Max or PLT42W-1 compact fluorescent (all lamps are included)

### Ballast:

Multi-tap – 120,208,240,277 Volts  
Universal – 120 -277 Volts

## Applications

- \* Parking areas
- \* Entrances
- \* Walkways
- \* Underpasses
- \* Loading docks
- \* Recreation areas

### Finish:

Dark bronze (BZ) powder paint finish is standard

### Approvals:



UNDERWRITERS  
LABORATORIES



Contact our engineering staff if you require further application information.

## Part Number Listing

Part No.	Series Number	Lamps	Ballast
R800128	WPS99-HPS150-MT-BZ	HPS150W	MT/60HZ
R800129	WPS99-MH100-MT-BZ	MH100W	MT/60HZ
R800013	WPS99-PLT421-UNV-BZ	PLT42W*1	120~277V 60HZ

\* Additional lamp wattages and ballast voltages are available. Contact factory for details.

Pulse Start units meet or exceed the minimum efficiency requirements of the Energy Independence and Security Act of 2007 (EISA)

\*\* Other finishes are available. Please contact the factory for details.

So that we may continue to supply the best possible product, specifications may change without notice. Consult the Paraflex website for the most up-to-date product information.

### Dimensions

